STEP 2: EASY7 SCE

2015年12月30日 15:18

HOW TO VIEW YOUR IP CAMERA USING EASY7 SCE:

1.Download / Install the free Easy7 Smart Client Express application to your computer:

📲 Windows Download

2.Login to the Easy7 SCE software. The default username and password are admin / 1111

| TIANDY | | |
|--------|--|--|
| | Easy Client | |
| | User Name admin Password •••• Nore | |

3.Next, to add a device, click on "Device"

| Easy7 | Rease Descret | | | | | A REAK |
|--|---|--|-------------------------------------|-------------------------|---|--|
| | | | | | | 0 |
| Operation | | | | | | |
| Preview Video preview | Playback search, playback and goverload video | Storage Status fieldy load video record and disk | Alarm theck slars information | | | |
| Configuration | | | | | | ŝ. |
| Device ferice/grue edits_elite and | User strate user suthority | Storage recording and template setting | System Setter refiguration | Cruine preter screen | Information display and confis device parameter | Event slars enting and activate configuration |
| Explored Actions | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | (almin) CPU Ph EAM Whi In-C-ST |

4.Click "Add Device" A new window will popup where you can add information to connect to your device.

| Eas | у7д ≜ | Jeroce . | | | | | | | | |
|---------------|--|----------------|-------------|----------------------|-----------------|---------|-------------|-----------|------|------------------------------|
| Net Dag | Attices | Padfy | Delate p | Remain Configuration | Invertibilities | Arthout | Aire Output | Operation | Devi | e li Turai ili Page 💦 👘 Page |
| Decode device | | | | | | | | | | |
| | AN Selected Device | modfy met 2x8s | | Invert Selection | | | | | | Drive device 2 |
| | P | Denius Tupe | Pat | Ownel to. | Enable | | | | | |
| | □ 20.30.00 □ 20.30.00 □ 20.00.00 | 154 154 | 3000 | 1 1 | 2.2 | | | | | |
| | | | | | | | | | 140 | |

5.Enter in your Device's information:

For the IP / Domain, be sure to enter the Device's IP Address that you will be connecting to. Once you have everything entered, including the device's username, password and the Device Details. After that is finished, you will click Add

| Encode device | Add Device | Modify | Delete | Remote Configuration Inve | ert Selection | | Device 0 Tota |
|---------------|---|--|---|---|---|----------|---------------|
| Decode device | Add Selected Device IP 10.30.10.10 10.30.10.86 | Modify Net Info Device Type TD-S TD-S TD-S | IP IP Refresh Port 3000 3000 | Add Device Madd Type Add Type Off-line Add Device Name Device Type Device IP Plock Device Port User Name Password Video Channel Alarm Input Alarm Output Import to Group | IP Type tiandy TD Series 80.80.80.118 3000 Admin 1 0 0 0 Add Cancel | Deration | |

6.Next, Go back to the Home and click Preview

| Easy7 🔮 😤 | ** |
|--|---------------|
| | |
| Statute Control of the second statute of the | |
| Configuration | |
| Derler State and | 144 #16 |
| Contract Instance | |
| | |
| | |
| | |
| | |
| (and (17) 19) | RAN DISCOURSE |

7.Lastly, double click on the device you just added on the right column to bring up the Preview

| Easv7 | | ۲ | Co. | 0 | | | A # - B × |
|---------------------|-----------------------|---------------|--------|---------|-------|-------|---|
| | Home | Preview | Device | Freview | Event | | |
| 2012/15/20 11:44:50 | | Channel 1 | | | | | Device List PTZ control |
| 2. J | A | | | | | | |
| | F | | | | | | |
| The Read Print | | | | | | | 🗌 🛵 10.30.10.10Alarm Input 1 |
| and the second | and the second second | | | | | | 🗌 🔬 10.30.10.10Alarm Output |
| | | 14 3 | | | | | |
| -640En | Motion De | tection Alarm | 500 B | | | 2402 | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| -24-64 | | | 549£1 | | | 500 | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| 240 | | | | | | 0.425 | * [|
| | | a) (55) (| | | | | Takback Status |
| | | | | | | | |
| | | | | | | | Laderia 1 (PT 014 DANE 7104 14-10-51 |