

HIK VISION

لیست قیمت رسمی آذر ۱۴۰۱

تارتن دژ آریانا

جشنواره آذر هایک ویژن

جهت اطلاع از تخفیف جشنواره هر محصول تماس بگیرید:

۰۲۱-۸۸۵۰۰۰۲۰



نمایندگی مرکزی محصولات هایک ویژن

1

2

3

4

5

6

Click for More information

DS-2CD1023G0E-I

DS-2CD1023G0-IUF

DS-2CD1043G0-I

DS-2CD1053G0-I

DS-2CD1057G0-L

DS-2CD1123G0E-I



Price (Rials)

۱۸,۲۴۰,۰۰۰

۲۷,۱۱۰,۰۰۰

۲۶,۸۸۰,۰۰۰

۳۱,۳۷۰,۰۰۰

۳۹,۱۸۰,۰۰۰

۱۹,۷۹۰,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Dome

Imaging Sensor

1/2.7" Prog. CMOS

1/2.7" Prog. CMOS

1/3" Prog. CMOS

1/2.7" Prog. CMOS

1/2.7" Prog. CMOS

1/2.8" Prog. CMOS

Resolution

2MP(1920x1080/30FPS)

2MP(1920x1080/30FPS)

4MP(2560x1440/20fps)

5MP (2560 × 1920/20fps)

5MP (2560 × 1920/20fps)

2MP(1920x1080/30FPS)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.01Lux @ F1.2

0.01Lux @ F2.0

0.01Lux @ F2.0

0.01Lux @ F2.0

0.001Lux @ F1.0

0.01Lux @ F1.2

Lens

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

Viewing Angle

112.1°/90.2°

112.1°/90.2°

98°/78.7°

98°/75.3°

95°/76°

114.8°/86°

IR Range

Up to 30m

Up to 30m (EXIR)

Up to 30m

Up to 30m (EXIR)

Up to 30m (Color Vu)

Up to 30m

Body Type & Standard

Plastic / IP67

Metal/Plastic / IP67

Plastic / IP67

Plastic / IP67

Metal / IP67

Plastic / IP67

SD Card Support

No

Yes (Up to 256G)

No

No

Yes (Up to 256G)

No

Microphone Support

No

Yes (Built in MIC)

No

No

No

No

WDR

DWDR

DWDR

DWDR

Yes (120db)

Yes (120db)

DWDR

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI, H.265+
COMP,PIR3D DNR, BLC, ROI, H.265+
COMP3D DNR, BLC, ROI, H.265+
COMP,PIR3D DNR, BLC, ROI, H.265+
COMP3D DNR, BLC, HLC, ROI, H.265+
COMP

3D DNR, BLC, H.265+ COMP

7

8

9

10

11

12

Click for More information

DS-2CD1323G0E-I

DS-2CD1323G0-IUF

DS-2CD1353G0-I

DS-2CD1357G0-L

DS-2CD1143G0-I

DS-2CD2021G1-I



Price (Rials)

۱۷,۸۷۰,۰۰۰

۲۷,۱۱۰,۰۰۰

۳۵,۵۳۰,۰۰۰

۳۹,۱۸۰,۰۰۰

۲۸,۷۹۰,۰۰۰

۳۳,۲۲۰,۰۰۰

Camera Type

Dome

Dome

Dome

Dome

Dome

Bullet

Imaging Sensor

1/2.7" Prog. CMOS

1/2.7" Prog. CMOS

1/2.7" Prog. CMOS

1/2.7" Prog. CMOS

1/3" Prog. CMOS

1/2.7" Prog. CMOS

Resolution

2MP(1920x1080/25FPS)

2MP(1920x1080/25FPS)

5MP(1920x1080/25FPS)

5MP(2560x1920/20FPS)

4MP(2560x1440/20fps)

2MP(1920x1080/25FPS)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.01Lux @ F2.0

0.028Lux @ F2.0

0.01Lux @ F2.0

0.001Lux @ F1.0

0.028Lux @ F2

0.005Lux @ F1.6

Lens

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

Viewing Angle

105°/81°

112.1°/90.2°

98.0°/75.3°

95°/76°

98°/78.7°

111.6°/91.5°

IR Range

Up to 30m (EXIR)

Up to 30m (EXIR)

Up to 30m (EXIR)

Up to 30m (Color Vu)

Up to 30m

Up to 30m (EXIR)

Body Type & Standard

Metal/Plastic / IP67

Metal/Plastic / IP67

Metal/Plastic / IP67

Metal/Plastic / IP67

Plastic / IP67

Metal/Plastic / IP67

SD Card Support

No

Yes (Up to 256G)

No

No

No

Yes (Up to 256 G)

Microphone Support

No

Yes (Built in MIC)

No

No

No

No

WDR

DWDR

DWDR

Yes (120db)

Yes (120db)

DWDR

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI, H.265+ COMP

3D DNR, BLC, ROI, H.265+ COMP

3D DNR, BLC, ROI, H.265+ COMP

3D DNR, BLC, ROI, H.265+ COMP

3D DNR, BLC, ROI, VCA, H.265+ COMP

3D DNR, BLC, H.265+ COMP

13

14

15

16

17

18

Click for More information

DS-2CD2525FWD-I

DS-2CD2H25FWD-IZS

DS-2CD2023G2-I

DS-2CD2027G2-L

DS-2CD2043G2-I

DS-2CD2047G2-L



Price (Rials)

۴۹,۸۴۰,۰۰۰

۸۳,۳۱۰,۰۰۰

۴۲,۸۱۰,۰۰۰

۴۷,۲۲۰,۰۰۰

۴۱,۸۰۰,۰۰۰

۴۷,۶۵۰,۰۰۰

Camera Type

Mini Dome

Dome

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/2.7" Prog. CMOS

1/2.7" Prog. CMOS

1/3" Prog. CMOS

1/1.8" Prog. CMOS

Resolution

2MP(1920x1080/25FPS)

2MP(1920x1080/25FPS)

2MP(1920x1080/25FPS)

2MP(1920x1080/25FPS)

4MP(2560x1440/30fps)

4MP(2560x1440/30fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.009Lux @ F1.6

0.005Lux @ F1.2

0.005Lux @ F1.6

0.005Lux @ F1.6

0.005Lux @ F1.6

0.0005Lux @ F1.0

Lens

2.8/4/6mm Fixed

2.8-12mm Motorized

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

Viewing Angle

108°/87°/53°

105°~35°

107°/87°

107°/87°

103°/84°

1097°/94°

IR Range

Up to 10m

Up to 30m

Up to 40m (EXIR)

Up to 40m (Color Vu)

Up to 40m

Up to 40m (Color Vu)

Body Type & Standard

Metal/Plastic/IP66/IK08

Metal / IP66/IK10

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

SD Card Support

Yes (Up to 128 G)

Yes (Up to 128 G)

Yes (Up to 256 G)

Yes (Up to 256 G)

Yes (Up to 256 G)

Yes (Up to 256 G)

Microphone Support

No

Yes (1.ch Audio Input)

No

No

No

No

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (130db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI, HLC, H.265+
COMP, DarkFighter3D DNR, BLC, ROI, HLC, H.265+
COMP, DarkFighter3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP

19

20

21

22

23

24

Click for More information

DS-2CD2063G2-I

DS-2CD2083G2-I

DS-2CD2087G2-LU

DS-2CD2123G2-I

DS-2CD2125FHWD-IS

DS-2CD2126G2-ISU



Price (Rials)

۴۶,۷۰,۰۰۰

۵۴,۸۱۰,۰۰۰

۹۴,۵۴۰,۰۰۰

۴۱,۹۲۰,۰۰۰

۴۹,۰۶۰,۰۰۰

۵۴,۲۰۰,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Dome

Dome

Dome

Imaging Sensor

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/1.2" Prog. CMOS

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

Resolution

6MP(3200x1800/20fps)

8MP(3072x1728/20fps)

8MP(3072x1728/20fps)

2MP(1920x1080/25FPS)

2MP(1920x1080/25FPS)

2MP(1920x1080/25FPS)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.005Lux @ F1.6

0.005Lux @ F1.6

0.0005Lux @ F1.0

0.005 Lux @ F1.6

0.005 Lux @ F1.6

0.002 Lux @ F1.4

Lens

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

Viewing Angle

107°/87°

107°/87°

102°/8°

107°/87°

108°/86.4°

107°/86°

IR Range

Up to 40m

Up to 40m

Up to 40m (ColorVu)

Up to 30m

Up to 30m

Up to 30m

Body Type & Standard

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67 & IK10

Metal / IP67 & IK10

Metal / IP67 & IK10

SD Card Support

Yes (Up to 256 G)

Yes (Up to 256 G)

Yes (Up to 256 G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 256G)

Microphone Support

No

No

No

No

Yes (Built in MIC)

Yes (Built in MIC)

WDR

Yes (120db)

Yes (120db)

Yes (130db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC, H.265+
COMP, AcuSense3D DNR, BLC, HLC, H.265+
COMP, AcuSense3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP, DarkFighter3D DNR, BLC, HLC, H.265+
COMP, DarkFighter

25

26

27

28

29

30

Click for More
information

DS-2CD2347G2-L

DS-2CD2143G2-IU

DS-2CD2163G2-IU

DS-2CD2183G2-IU

DS-2CD2T43G2-4I

DS-2CD2T63G2-4I



Price (Rials)

۵۲,۴۶۰,۰۰۰

۴۴,۹۸۰,۰۰۰

۴۶,۸۷۰,۰۰۰

۵۱,۶۵۰,۰۰۰

۵۰,۷۵۰,۰۰۰

۵۵,۰۵۰,۰۰۰

Camera Type

Dome

Dome

Dome

Dome

Bullet

Bullet

Imaging Sensor

1/1.8" Prog. CMOS

1/3" Prog. CMOS

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/3" Prog. CMOS

1/2.8" Prog. CMOS

Resolution

4MP(2688 × 1520/25fps)

4MP(2688 × 1520/25fps)

6MP(3200 × 1800/25fps)

8MP(3840 × 2160/25fps)

4MP(2688×1520/25fps)

6MP(3200×1800/25fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.0005 Lux @ F1.0

0.005 Lux @ F1.6

0.005 Lux @ F1.6

0.005 Lux @ F1.6

0.005Lux @ F1.6

0.005Lux @ F1.6

Lens

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

Viewing Angle

112°/95°

103°/84°

107°/87°

107°/87°

103°/84°

107°/87°

IR Range

Up to 30m (Color Vu)

Up to 30m

Up to 30m

Up to 30m

Up to 80m (EXIR)

Up to 80m (EXIR)

Body Type & Standard

Metal / IP67

Metal / IP67 & IK10

Metal / IP67 & IK10

Metal / IP67 & IK10

Metal / IP67

Metal / IP67

SD Card Support

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 256G)

Microphone Support

No

Yes (Built in MIC)

No

Yes (Built in MIC)

No

No

WDR

Yes (130db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, ROI, H.265+
COMP3D DNR, BLC, ROI, H.265+
COMP

31

32

33

34

35

36

Click for More information

DS-2CD2T66G2-2I

DS-2CD2T83G2-4I

DS-2CD1643G0-IZ

DS-2CD1743G0-IZ

DS-2CD2625FWD-IZS

DS-2CD2643G2-IZS



Price (Rials)

۵۸,۹۸۰,۰۰۰

۵۷,۶۷۰,۰۰۰

۵۲,۵۹۰,۰۰۰

۵۹,۰۸۰,۰۰۰

۸۹,۹۴۰,۰۰۰

۸۱,۹۴۰,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Dome

Bullet

Bullet

Imaging Sensor

1/2.4" Prog. CMOS

1/2.5" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/2.8" Prog. CMOS

1/3" Prog. CMOS

Resolution

6MP(3200 × 1800/25fps)

8MP(3840 × 2160/15fps)

4MP(2560 × 1440/20fps)

4MP (2560x1440/20fps)

2MP(1920 × 1080/25fps)

4MP(2688 × 1520/25fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.003Lux @ F1.6

0.005Lux @ F1.2

0.005Lux @ F1.6

0.005Lux @ F1.6

0.005Lux @ F1.6

0.005Lux @ F1.6

Lens

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm Motorized

Viewing Angle

105.1°/83.9°

102°/79°

102°~31°

91.2°~28.3°

105°~35°

95.8°~29.2°

IR Range

Up to 60m

Up to 80m (EXIR)

Up to 50m (EXIR)

Up to 30m (EXIR)

Up to 50m

Up to 60m

Body Type & Standard

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP66,IK10

Metal / IP67,IK10

SD Card Support

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 128G)

Yes (Up to 256G)

Microphone Support

No

No

No

No

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC, ROI, H.265+ COMP, DarkFighter

3D DNR, BLC, HLC, H.265+ COMP, ROI

3D DNR, BLC, ROI, H.265+ COMP

3D DNR, BLC, H.265+ COMP

3D DNR, BLC, ROI, H.265+ COMP, DarkFighter

3D DNR, BLC, ROI, H.265+ COMP

37

38

39

40

Click for More information

DS-2CD2683G2-IZS

DS-2CD2685FWD-IZS

DS-2CD2743G2-IZS

DS-2CD2786G2-IZS



Price (Rials)

۹۰,۶۹۰,۰۰۰

۱۲۴,۰۸۰,۰۰۰

۸۱,۹۴۰,۰۰۰

۱۳۰,۲۷۰,۰۰۰

Camera Type

Bullet

Bullet

Dome

Dome

Imaging Sensor

1/2.8" Prog. CMOS

1/2.5" Prog. CMOS

1/3" Prog. CMOS

1/1.8" Prog. CMOS

Resolution

8MP(3840 × 2160/20fps)

8MP(3840 × 2160/20fps)

4MP (2560x1440/20FPS)

8MP(3840 × 2160/20fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.005Lux @ F1.6

0.01Lux @ F1.2

0.005Lux @ F1.6

0.003Lux @ F1.4

Lens

2.8-12mm Motorized

2.8-12mm

2.8-12mm Motorized

2.8-12mm Motorized

Viewing Angle

108°~30°

115°~35°

104°~29°

108°~46°

IR Range

Up to 60m

Up to 50m

Up to 40m

Up to 40m

Body Type & Standard

Metal / IP67,IK10

Metal / IP67,IK10

Metal / IP67,IK10

Metal / IP66,IK10

SD Card Support

Yes (Up to 256G)

Yes (Up to 128G)

Yes (Up to 128G)

Yes (Up to 256G)

Microphone Support

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC,HLC, ROI, H.265+ COMP, Deep Learning

3D DNR, BLC,HLC, ROI, H.265+ COMP, Deep Learning

3D DNR, BLC, H.265+ COMP, Deep Learning

3D DNR, BLC, HLC, H.265+ COMP, Deep Learning, DarkFighter

41

42

43

44

45

46

Click for More information

DS-2CD2955FWD-I

DS-2DE4225IW-DE T5

DS-2DE4425IW-DE T5

DS-2DE5220IW-AE

DS-2DE4A320IW-DE

DS-2DF5276-AE3



Price (Rials)

1٠٧,1٢٠,٠٠٠

1٣٩,٧٣٠,٠٠٠

1٧٩,٢٠٠,٠٠٠

٢٣1,1٧٠,٠٠٠

٢٧٢,1٧٠,٠٠٠

٢٧٩,٩٩٠,٠٠٠

Camera Type

Fisheye

PTZ

PTZ

PTZ

PTZ

PTZ

Imaging Sensor

1/2.5" Prog. CMOS

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/3" Prog. CMOS

Resolution

5MP(2560 × 1920/30FPS)

2MP(1920x1080/60FPS)

4MP(2560 × 1440/30FPS)

2MP(1920x1080/60FPS)

3MP(2048x1536/25FPS)

1.3MP(1280x960/30FPS)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.01Lux/F1.2

0.005Lux/F1.6

0.005Lux/F1.6

0.02Lux/F1.5

0.05Lux/F1.6

0.05Lux/F1.6

Lens

1.05mm

4.8-120mm Motorized

4.8-120mm Motorized

4.7-94mm

4.7-94mm

4.3-129mm

Viewing Angle

180°

25x

25x

20x

20x

30x

IR Range

Up to 8 m

Up to 100m

Up to 100m

Up to 150m

Up to 50m

-

Body Type & Standard

Metal

Metal/IP66

Metal/IP66

IP66, IK10

IP66

IP66

SD Card Support

Yes (Up to128G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to128G)

Yes (Up to128G)

Yes (Up to 128G)

Microphone Support

No

No

No

No

No

No

WDR

Yes (120db)

Yes (120db)

Yes (120db)

DWDR

WDR

DWDR

WIFI

No

No

No

No

No

No

Power Supply

12VDC & POE(802.3at)

12 VDC & POE(802.3at)

12 VDC & POE(802.3at)

High-PoE&24 VAC

12 VDC & POE(802.3at)

High-PoE / PoE+ / 24VAC

Other Features

3D DNR, H.265+

16x Digital Zoom, H.265+, HLC, BLC, 3D DNR

16x Digital Zoom, H.265+, HLC, BLC, 3D DNR

16x Digital Zoom, H.265+, HLC, BLC, 3D DNR, Defog

16x Digital Zoom, H.265+, HLC, BLC, 3D DNR

16x Digital Zoom, H.265+, HLC, BLC, 3D DNR, Defog

47

48

Click for More
information

DS-2DF5276-AEL

DS-2DF6A236X-AEL



Price (Rials)

۴۴۷,۴۵۰,۰۰۰

۵۲۰,۸۰۰,۰۰۰

Camera Type

PTZ

PTZ

Imaging Sensor

1/3" Prog. CMOS

1/1.8" Prog. CMOS

Resolution

1.3MP(1280x960/30FPS)

2MP(1920x1080/25FPS)

Network Standard

ONVIF

ONVIF

Min. Illustration

0.05Lux/F1.6

0.002Lux/F1.5

Lens

4.3-129mm

5.7-205.2mm

Viewing Angle

30x

36x

IR Range

-

-

Body Type & Standard

IP66

Metal/IP67/IK10

SD Card Support

Yes (Up to128G)

Yes (Up to128G)

Microphone Support

No

No

WDR

DWDR

Yes (120db)

WIFI

No

No

Power Supply

High-PoE / PoE+ / 24VAC

High-PoE / 24VAC

Other Features

12x Digital Zoom, H.265+, HLC,
BLC, 3D DNR, Defog

12x Digital Zoom, H.265+, HLC,
BLC, 3D DNR, Defog, EIS,
Darkfighter

49

50

51

52

53

54

Click for More information

DS-7104NI-Q1/M

DS-7108NI-Q1/M

DS-7604NI-K1

DS-7604NI-K1/4P

DS-7608NI-K1

DS-7608NI-K1/8P



Price (Rials)

۲۶,۸۶۰,۰۰۰

۲۹,۸۲۰,۰۰۰

۴۲,۷۹۰,۰۰۰

۴۹,۹۷۰,۰۰۰

۴۶,۷۷۰,۰۰۰

۶۹,۰۹۰,۰۰۰

NVR Type

4 Ch

8 Ch

4 Ch

4 Ch / 4POE

8 Ch

8 Ch / 8POE

Input BandWidth

40Mbps

60Mbps

40Mbps

40Mbps

80Mbps

80Mbps

Output Bandwidth

60Mbps

60Mbps

80Mbps

80Mbps

80Mbps

80Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

Decoding Capacity

Upto 4Mp

Upto 4Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Video Output

1 Port HDMI : 1080p
1 Port VGA1 Port HDMI : 1080p
1 Port VGA1 Port HDMI : 4k
1 Port VGA1 Port HDMI : 4k
1 Port VGA1 Port HDMI : 4K
1 Port VGA : 1080P1 Port HDMI : 4K
1 Port VGA : 1080P

POE Ports

-

-

-

4 POE Ports

-

8 POE Ports

SATA Interface

1 HDD up to 6TB

1 HDD up to 6TB

1 HDD up to 8TB

1 HDD up to 8TB

1 HDD up to 8TB

1 HDD up to 8TB

Network Interface

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

Chassis

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Other Features

H.265+ COMP

H.265+ COMP

H.265+ COMP

H.265+ COMP

H.265+ COMP
Alarm I/O 4/1

H.265+ COMP

55

56

57

58

59

60

Click for More information

DS-7616NI-Q2/16P

DS-7716NI-Q4

DS-7716NI-Q4/16P

DS-7616NI-K2

DS-7716NI-K4

DS-7732NI-K4



Price (Rials)

1٠٧,٤٧٠,٠٠٠

11٨,٣٨٠,٠٠٠

1٧٠,٥٨٠,٠٠٠

٥٩,٤٧٠,٠٠٠

11٩,٦٤٠,٠٠٠

1٥٠,٧٢٠,٠٠٠

NVR Type

16 Ch / 16 POE

16 Ch

16 Ch / 16 POE

16 Ch

16 Ch

32 Ch

Input BandWidth

160Mbps

160Mbps

160Mbps

160Mbps

200Mbps

256Mbps

Output Bandwidth

80Mbps

80Mbps

80Mbps

160Mbps

160Mbps

160Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

Decoding Capacity

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 12Mp

Upto 8Mp

Video Output

1 Port HDMI : 4k
1 Port VGA : 1920P1 Port HDMI : 4k
1 Port VGA1 Port HDMI : 4k
1 Port VGA1 Port HDMI : 4K
1 Port VGA : 1080P1 Port HDMI : 4k
1 Port VGA1 Port HDMI : 4K
1 Port VGA : 1080P

POE Ports

16 POE Ports

-

16 POE Ports

-

-

-

SATA Interface

2 HDD up to 8TB

4 HDD up to 8TB

4 HDD up to 8TB

2 HDD up to 8TB

4 HDD up to 10TB

4 HDD up to 8TB

Network Interface

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

2 RJ45 1000M

2 RJ45 1000M

Chassis

1U chassis

1.5U

1.5U

Standalone 1U

1.5U

19" 1.5 Case

Other Features

H.265+ COMPR

H.265+ COMPR
Alarm I/O 16/4H.265+ COMPR
Alarm I/O 16/4H.265+ COMPR
Alarm I/O 4/1H.265+ COMPR
Alarm I/O 16/41H.265+ COMPR
Alarm I/O 16/4

61

62

63

64

65

66

Click for More information

DS-7732NI-K4/16P

IDS-7732NXI-I4/8S

DS-9632NI-I8

IDS-9632NXI-I8/4F

DS-9664NI-I8

DS-9664NI-I16



Price (Rials)

۲۲۶,۵۴۰,۰۰۰

۴۳۴,۲۶۰,۰۰۰

۵۰۹,۱۶۰,۰۰۰

۱,۹۴۰,۷۰۰,۰۰۰

۶۸۲,۵۳۰,۰۰۰

۱,۰۲۹,۱۶۰,۰۰۰

NVR Type

32 Ch / 16 POE

32 Ch

32 Ch

32 Ch

64 Ch

64 Ch

Input BandWidth

256Mbps

320Mbps

320Mbps

320Mbps

320Mbps

320Mbps

Output Bandwidth

160Mbps

256Mbps

256Mbps

256Mbps

256Mbps

256Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 2Ch. Out

1Ch. In/ 2Ch. Out

1Ch. In/ 2Ch. Out

1Ch. In/ 2Ch. Out

Decoding Capacity

Upto 8Mp

Upto 12Mp

Upto 12Mp

Upto 12Mp

Upto 12Mp

Upto 12Mp

Video Output

1 Port HDMI : 4K
1 Port VGA : 1080P1 Port HDMI : 4K
1 Port VGA : 1080P2 Port HDMI : 4K/1080P
1 Port VGA : 1080P1 Port HDMI : 1080P
1 Port VGA : 1080P2 Port HDMI : 4K/1080P
2 Port VGA : 1080P2 Port HDMI : 4K/1080P
2 Port VGA : 1080P

POE Ports

16 POE Ports

-

-

-

-

-

SATA Interface

4 HDD up to 8TB

4 HDD up to 10TB

8 HDD up to 10TB

8 HDD up to 10TB

8 HDD up to 10TB

16 HDD up to 10TB

Network Interface

1 RJ45 1000M

2 RJ45 1000M

2 RJ45 1000M

2 RJ45 1000M

2 RJ45 1000M

2 RJ45 1000M

Chassis

19" 1.5 Case

19" 1.5 Case

19" 1.5 Case

2U

3U

3U

Other Features

H.265+ COMPR
Alarm I/O 16/4H.265+ COMPR
Alarm I/O 16/8H.265+ COMPR
Alarm I/O 16/4, RAIDH.265+ COMPR
Alarm I/O 16/4, RAID,
DeepinMindH.265+ COMPR
Alarm I/O 16/4, RAIDH.265+ COMPR
Alarm I/O 16/4, RAID