

DH-HAC-HFW1500TH-I4

5MP Starlight HDCVI IR Bullet Camera



* The parameters and datasheets below can only be applied to 1500-S2 series.

- Max 25 fps@5MP (16:9 video output)
- CVI/CVBS/AHD/TVI switchable
- 3.6 mm fixed lens (6 mm optional)
- Max. IR length 40 m, Smart IR
- IP67, 12V DC



System Overview

Experience 5MP full HD video and the simplicity of using existing cabling infrastructure with HDCVI. The Lite series 5MP HDCVI camera features a compact design and offers a high quality image at a friendly price. It offers various motorized/fixed lens models with a multi-language OSD and HD/SD switchable output. Its structural flexibility and high cost-performance make the camera an ideal choice for SMB solutions.

Functions

4 Signals over 1 Coaxial Cable

HDCVI technology supports 4 signals to be transmitted over 1 coaxial cable simultaneously, i.e. video, audio*, data and power. Dual-way data transmission allows the HDCVI camera to interact with the XVR, such as sending control signal or triggering alarm. Moreover, HDCVI technology supports PoC for construction flexibility.

* Audio input is available for some models of HDCVI cameras.

Long Distance Transmission

HDCVI technology guarantees real-time transmission at long distance without any loss. It supports up to 700 m for 5MP HD video through coaxial cable, and up to 300 m through UTP cable.*

*Actual results verified by real-scene testing in Dahua's test laboratory.

Simplicity

HDCVI technology inherits the born feature of simplicity from traditional analog surveillance system, making itself a best choice for investment protection. HDCVI system can seamlessly upgrade the traditional analog system without replacing existing coaxial cabling. The plug and play approach enables full HD video surveillance without the hassle of configuring a network.

Smart IR

The camera is designed with IR LED illumination for best lowlight performance. Smart IR is a technology to ensure brightness uniformity in B/W image under low illumination. Dahua's unique Smart IR adjusts to the intensity of camera's infrared LEDs to compensate for the distance of an object, and prevents IR LEDs from overexposing images as the object comes closer to the camera.

Multi-formats

The camera supports multiple video formats including HDCVI, CVBS and other two common HD analog formats in the market. The four formats can be switched over through OSD menu. This feature makes the camera compatible with most end users' existing HD/SD DVRs.

Multi-language OSD


OSD menu provides multiple image adjustments and function settings to meet the requirements of different monitoring scenes. The OSD menu includes configurations such as backlight mode, day/night, white balance, privacy mask and motion detect. The camera supports 11 languages for OSD menu, namely, Chinese, English, French, German, Spanish, Portuguese, Italian, Japanese, Korean, Russian and Polish.

Protection


The camera's outstanding reliability is unsurpassed due to its rugged design. The camera is protected against water and dust with IP67 ranking, making it suitable for indoor or outdoor environments. With working temperature range of -40 °C to +60 °C (-40 °F to +140 °F), the camera is designed for extreme temperature environments. Supporting ±30% input voltage tolerance, this camera suits even the most unstable power supply conditions. Its 4kV lightning rating provides protection against the camera and its structure from the effects of lightning.

Technical Specification						Day/Night		Auto switch by ICR	
Dahua Camera						BLC		BLC/HLC/DWDR	
Image Sensor		1/2.7 inch CMOS				WDR		DWDR	
Max. Resolution		2880 (H) × 1620 (V)				White Balance		Auto; manual	
Pixel		5MP				Gain Control		Auto; manual	
Scanning System		Progressive				Noise Reduction		2D NR	
Electronic Shutter Speed		PAL: 1/25 s–1/100,000 s NTSC: 1/30 s–1/100,000 s				Smart IR		Yes	
S/N Ratio		> 65 dB				Mirror		Off/On	
Min. Illumination		0.005 Lux/F1.6, 30IRE, 0 Lux IR on				Privacy Masking		Off/On (8 areas, rectangle)	
Illumination Distance		40 m (131.2 ft)				Certifications			
Illumination On/Off Control		Auto; manual				Certifications			
Illuminator Number		1				CE (EN 55032:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 55024:2010+A1:2015, EN 55035:2017, EN 50130-4:2011+A1:2014, EN 62368-1:2014+A11:2017) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)			
Pan/Tilt/Rotation Range		Pan: 0°–360° Tilt: 0°–180° Rotation: 0°–360°				Port			
Lens						Video Output			
Lens Type		Fixed-focal				Video output choices of CVI/TVI/AHD/CVBS by one BNC port			
Mount Type		M12				Power			
Focal Length		3.6 mm; 6 mm				Power Supply		12V ±30% DC	
Max. Aperture		F1.6				Power Consumption		Max 3.2W (12V DC, IR on)	
Field of View		3.6 mm: 109° × 92° × 48° (diagonal × horizontal × vertical) 6 mm: 65° × 57° × 30° (diagonal × horizontal × vertical)				Environment			
Iris Type		Fixed iris				Operating Temperature		–40°C to +60°C (–40°F to 140°F); < 95% (non-condensation)	
Close Focus Distance		3.6 mm: 1.6 m (5.2 ft) 6 mm: 3.1 m (10.2 ft)				Storage Temperature		–40°C to +60°C (–40°F to 140°F); < 95% (non-condensation)	
DORI Distance	Lens	Detect	Observe	Recognize	Identify	Protection Grade			
	3.6 mm	80 m (262.5 ft)	32 m (105.0 ft)	16 m (52.5 ft)	8 m (26.2 ft)	IP67			
	6 mm	120 m (393.7 ft)	60.2 m (197.5 ft)	24 m (78.7 ft)	12 m (39.4 m)	Structure			
	*DORI (Detect, Observe, Recognize, Identify) is a standard system (EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area. The numbers in this table do not reflect intelligent function distances. For intelligent function distances, refer to installation and commissioning manual/project design tool.					Casing			
Video						Camera Dimensions		Mental front cover+plastic main body+mental bracket	
Frame Rate		CVI: PAL: 5M@25 fps; 4M@25 fps; 1080P@25 fps; NTSC: 5M@25 fps; 4M@30 fps; 1080P@30 fps AHD: PAL: 4M@25 fps; NTSC: 4M@30 fps TVI: PAL: 4M@25 fps; NTSC: 4M@30 fps CVBS: PAL: 960H; NTSC: 960H				Net Weight		240.7 mm × 90.7 mm × 90.4 mm (9.48" × 3.57" × 3.56") 0.41 kg (0.90 lb)	
Resolution		5M (2880 × 1620); 4M (2560 × 1440); 1080P (1920 × 1080); 960 H (960 × 576/960 × 480)				Gross Weight		0.64 kg (1.41 lb)	

Ordering Information		
Type	Part Number	Description
SMP Camera	DH-HAC-HFW1500THP-I4 3.6 mm	5MP HDCVI IR Bullet Camera
	DH-HAC-HFW1500THN-I4 3.6 mm	
	DH-HAC-HFW1500THP-I4 6 mm	
	DH-HAC-HFW1500THN-I4 6 mm	
Accessories	PFA135	Junction Box
	PFA130-E	IP66 Junction Box (For use alone or with PFA152-E pole mount)
	PFA152-E	Pole Mount Bracket (For use with PFA130-E junction box)
	PFM800-4K	Passive HDCVI Balun
	PFM321D	12V 1A Power Adapter
	PFM820 (Only 1080P and below are available)	UTC Controller
	PFM904	Integrated Mount Tester



Dimensions (mm[inch])



Accessories

Optional:



PFA135
Junction Box



PFA130-E
IP66 Junction Box
(For use alone or with
PFA152-E pole mount)



PFA152-E
Pole Mount Bracket
(For use with PFA130-E
junction box)



PFM800-4K
Passive HDCVI Balun



PFM321D
12V 1A Power Adapter



PFM820
UTC Controller



PFM904
Integrated Mount Tester