# Yealink



### Yealink DECT IP Phone

- · High-performance SIP cordless phone system
- 1.8" 128 x 160 TFT color screen with intuitive user interface
- · Up to 20 simultaneous calls
- Up to 10 DECT cordless handsets
- · Up to 10 SIP accounts
- Support Opus audio codec
- · Noise Reduction System
- FNR (Flexible Noise Reduction)
- Up to 35-hour talk time (in ideal conditions)
- Up to 400-hour standby time (in ideal conditions)
- · Quick charging: 10-min charge time for 2-hour talk time
- · TLS and SRTP security encryption
- · Headset connection via 3.5 mm jack
- · Charger wall mountable



Simultaneous Calls

Security Encryption

- Deployment
- Standby Time

The Yealink W73P, being a high-performance SIP cordless phone system, which can register 10 Yealink DECT W73H handsets, is the ideal solution for small and medium-sized businesses. It allows you to enjoy superb mobility and efficient flexibility immediately as well as significantly eliminates additional wiring troubles and charges. Featuring more functions, lines and mobility, it supports up to 10 SIP accounts and 20 simultaneous calls, improving signal strength and responsiveness to provide a stable and good experience for your mobile communications.

You can enjoy clearer, high-quality voice calls because of the new Noise Cancellation technology. By supporting Opus codec, W73P consistently delivers excellent and professional audio quality in both high-bandwidth and poor network conditions. It brings a seamless call management for our users while "on-the-go" with combining DECT technology with SIP capabilities. Enjoy the convenience of wireless communication anytime, anywhere, as well as the extensive benefits and feature richness of IP voice phones.

The Yealink DECT IP phone W73P supports efficient provisioning and effortless mass deployment with Yealink's Redirection and Provisioning Service (RPS) and Boot mechanism to help you realize the Zero Touch Provisioning without any complex manual settings, which makes it simple to deploy, easy to maintain and upgrade, saving even more time and IT costs for businesses.



- · Up to 10 DECT cordless handsets and 10 SIP accounts
- · Up to 20 simultaneous calls to ensure that each handset can make two calls
- DECT radio coverage up to 50m indoors and 300m outdoors
- Energy-saving ECO features

#### **DECT** technology:

Yealink DECT technology is based on CAT-iq2.0, which focuses on high quality Audio VoIP (wideband), as well as low bit - rate data applications. But we are not compatible with any third-party DECT devices (base station, handset, etc.).

## Yealink

### Specifications W73P

#### Phone Features

- > Up to 20 simultaneous calls
- > Up to 10 handsets
- > Up to 10 SIP accounts
- > Up to 2 simultaneous calls per handset
- > Up to 5 repeaters per base station (RT20U)
- > Up to 6 repeaters per base station (RT30)
- > Handset selection for receiving call
- Handset and number selection for placing call
- > Paging, intercom, auto answer, dial plan
- > Call hold, call transfer, 3-way conference
- > Switching between calls
- > Call waiting, mute, silence, DND
- > Caller ID with name and number
- > Anonymous call, Anonymous call rejection
- > Call forward (always/busy/no answer)
- > Speed dial, voicemail, redial
- Message Waiting Indication (MWI)
  Music on hold (server-based)
- Local phonebook for up to 1000 entries(store in the base)
- > Remote phonebook/LDAP/XML phonebook
- > Phonebook search/import/export> 100 call history per handset:
- All/Placed/Missed/Received > Direct IP call without SIP proxy
- Reset to factory, reboot
- Keypad lock, emergency call
- Resplay lock, energency can
  Broadcoff directory, BroadCoff of
- > Broadsoft directory, BroadSoft call log> Broadworks feature key synchronization
- Shared Call Appearance (SCA)
- > XMI browser

#### Personalization

- > 9 ringer melodies
- > Screen saver
- > Multilingual user interface

#### Management

Compliance

- > Auto-provision via
- TFTP/FTP/HTTP/HTTPS/RPS
- > Auto-provision with PnP
- > Handset upgrade: OTA (Over-The-Air)
- > Configuration: browser/phone/auto-provision
- > Trace package and system log export

#### Audio Features

- > Full-duplex speakerphone
  - > Hearing Aid Compatibility (HAC) compliant
  - > FNR (Noise Cancellation)
  - > Receiver volume control: 5 steps
  - > Ringer volume control: 5 steps+off
  - > Multiple advisory tones
  - > Acoustic warning for low battery status
  - > DTMF
  - > Wideband codec: Opus, AMR-WB (optional), G.722
  - > Narrowband codec: PCMU, PCMA, G.726, G.729, G.729A, iLBC
  - G.729A, ILBC
- > VAD, CNG, AGC, PLC, AJB
- > AEC (supported by W73H)
- > Support VQ-RTCPXR (RFC6035), RTCP-XR

#### Network Features

- > SIP v1 (RFC2543), v2 (RFC3261)
- > SNTP/NTP
- > VLAN (802.1Q and 802.1P)
- > 802.1x, LLDP
- > STUN Client (NAT Traversal)
- > UDP/TCP/TLS
- > IP assignment: static/DHCP
- > Support outbound proxy server backup

#### Security

#### > Open VPN

- > Transport Layer Security (TLS)
- > HTTPS (server/client), SRTP (RFC3711)
- > Digest authentication
- > Secure configuration file via AES encryption
- > Support SHA256/SHA512/SHA384
- > Three-level configuration mode: Admin/Var/User

#### DECT

- > Frequency bands:
- 1880 1900 MHz (Europe), 1920 1930 MHz (US)
- > DECT Standards: CAT-iq2.0

#### Interface

REACH ISO 9001 💩 🎒 😽 broadsoft 3OX

YEALINK NETWORK TECHNOLOGY CO., LTD

- > 1 x RJ45 10/100M Ethernet port
- > Power over Ethernet (IEEE 802.3af), Class 1

Asterisk<sup>®</sup> Compatible

> Headset jack (3.5 mm)

#### Physical Features

- > Indoor Range: 50m (in ideal conditions)
- > Outdoor Range: 300m (in ideal conditions)
- > Standby Time: 400 hours (in ideal conditions)
- > Talk Time: 35 hours (in ideal conditions)
- > 1.8" 128 x 160-pixel TFT color display
- > Desktop or wall mountable
- > LCD backlight, key backlight
- > Energy-saving ECO mode/ECO Mode+
- > Backlit keypad with 25 keys:
- Standard ITU telephone keypad, 12 keys, 4x3, with star and pound key
  - 5 navigation keys (left, right, up, down, OK)
  - 2 softkeys
  - 6 function keys (Speaker, message, Off-hook,

> External Yealink AC adapter: AC 100-240V Input

> Color: Handset: Space Grey; Base: Classic Grey

Base station size: 130mm x 100mm x 25.1mm

Operating temperature: -10~+50°C (+14~122°F)

Storage temperature: -30 ~ 70°C (-22 ~ 158°F)

> Handset size: 144.5 mm x 48 mm x 21 mm

- Cancel, TRAN, Mute)
- > 6 shortcut keys

>

>

Package Features

> Package content:

- W73H Handset

- Charger Cradle

- Ethernet Cable

- Belt Clip

>

Email: sales@yealink.com

- W70B Base Station - Base Stand

- Two Power Adapters

- Rechargeable Battery

Giftbox size: 502mm × 362mm × 215mm

Carton meas: 205mm × 176mm × 95mm

Web: www.yealink.com

- Quick Start Guide

> Qty/CNT: 10 PCS

> N.W: 6.854Kg> G.W: 7.53Kg

- > Three LED indicators on W70B:
  - 1 x Registration LED
  - 1 x Network Status LED

Operating humidity: 10~95%

and DC 5V/0.6A Output