

# Yealink W76P

W76P

### Mid-level DECT IP Phone System













Long Standby Tir



Designed to fulfill the demands of mobile communication in modern business workplaces, Yealink W76P combines the W56H DECT handset and W70B base station for superb audio quality and cordless communication experience, which makes it an ideal solution for diverse business segments of small to medium size.

#### Optimized Experience for Your On-the-move Callings


With the professional handset, sophisticated acoustic technology, as well as the enhanced computing capacity, the W76P provides the users with stable network and signal performance, exceptional audio clarity, faster response and improved adaptability for complicated environments.

In addition, the W76P is of remarkable power efficiency with long battery life and quick charge support, which helps in optimizing user experience with more flexibility and ease.



#### Robust System, Productivity-enhancing Performance

Supporting registration with up to 10 Yealink W76P DECT handsets, the W76P system is launched with reinforced processing capacity for up to 10 SIP accounts and 20 simultaneous calls. More flexibility and mobility could be enabled through up to 6 optional repeaters for extended network coverage.



#### Well-designed Handset, Featured for Everyday Business


Combining a vivid color screen with the dedicated modern stylish appearence, Yealink W56H DECT handset fits common business workspaces while brings rich telephony features and best-in-class experience in cordless communication.





Quick access to call handling and key features via the classic keypad







Embedded powerful Liion battery to undertake heavy call loads

### More Choices with Yealink Full Range of DECT Devices Solution

Compatible with the whole series of Yealink DECT endpoints including the handsets, conference phones and DD phones, the W76P could be scaled for building up wireless communication networks in various workspaces.



#### Streamline Provision and Management, Saving Your Labor and Time Costs

The W76P supports efficient provisioning and effortless mass deployment with Yealink's Redirection and Provisioning Service (RPS) and Boot mechanism to help realize remote deployment, maintenance and upgrade.



## Yealink W76P Specification

General Features	
Indoor range	50m (in ideal conditions)
Outdoor range	300m (in ideal conditions)
Standby time (in ideal conditions)	400 hours
Talk time (in ideal conditions)	30 hours
Battery	Lithium
Display (W56H)	2.4" TFT color display
Wall mountable	
Multilingual user interface	

Talanhana Fashana	
Telephony Features	
Simultaneous calls	Up to 20
Handsets	Up to 10
SIP accounts	Up to 10
Simultaneous calls per handset	Up to 2
Repeaters per base station (RT20U)	Up to 5
Repeaters per base station (RT30)	Up to 6
3-way conference	
Ringer melodies	9
Audio Features	
HD voice	
Full-duplex speakerphone	

HD voice	
Full-duplex speakerphone	
Hearing Aid Compatibility (HAC) compliant	
ACE	(supported by W56H)
Wideband codec	G.722, AMR-WB (optional)
Narrowband codec	PCMU, PCMA, G.726, G.729, G.729A, iLBC

Interface	
Headset jack	3.5 mm
Ethernet port	1 x RJ45 10/100M
Power over Ethernet (IEEE 802.3af), class 1	
External Yealink AC adapter	AC 100-240V Input DC 5V/600mA Output
DECT	
Frequency bands	1880 – 1900 MHz (Europe) 1920 – 1930 MHz (US)

Security	
Transport Layer Security (TLS)	
HTTPS (server/client), SRTP (RFC3711)	
Open VPN	
Digest authentication	
Secure configuration file via AES encryption	
SHA256/SHA512/SHA384	
Three-level configuration mode	Admin/Var/User
Management	
Auto-provision	TFTP/FTP/HTTP/HTTPS/RPS
Handset upgrade	OTA (Over-The-Air)

