

DH-HAC-HDW1200TL-A

2MP HDCVI IR Eyeball Camera



- Max 30fps@1080P
- HD and SD output switchable
- 3.6mm fixed lens (2.8mm optional)
- Built-in mic
- Max. IR length 30m, Smart IR
- IP67, DC12V



System Overview

Experience 1080P full HD video and the simplicity of using existing cabling infrastructure with HDCVI. The Lite series 1080P HDCVI camera features a compact design and offers a high quality image at a friendly price. It offers various motorized/fixed lens models with a multi-language OSD and HD/SD switchable output. Its structural flexibility and high cost-performance makes the camera an ideal choice for SMB solutions.

Functions

4 Signals over 1 Coaxial Cable

HDCVI technology supports 4 signals to be transmitted over 1 coaxial cable simultaneously, i.e. video, audio*, data and power. Dual-way data transmission allows the HDCVI camera to interact with the XVR, such as sending control signal or triggering alarm. Moreover, HDCVI technology supports PoC for construction flexibility.

* Audio input is available for some models of HDCVI cameras.

Long Distance Transmission

HDCVI technology guarantees real-time transmission at long distance without any loss. It supports up to 800m(1080p)/1200m(720P) transmission via coaxial cable, and up to 300m(1080P)/450m(720P) via UTP cable.*

*This function is available for select models.

Simplicity

HDCVI technology inherits the born feature of simplicity from traditional analog surveillance system, making itself a best choice for investment protection. HDCVI system can seamlessly upgrade the traditional analog system without replacing existing coaxial cabling. The plug and play approach enables full HD video surveillance without the hassle of configuring a network.

Smart IR

The camera is designed with IR LED illumination for best lowlight performance. Smart IR is a technology to ensure brightness uniformity in B/W image under low illumination. Dahua's unique Smart IR adjusts to the intensity of camera's infrared LEDs to compensate for the distance of an object, and prevents IR LEDs from overexposing images as the object come closer to the camera.

Multi-formats

The camera supports multiple video formats including HDCVI, CVBS and other two common HD analog formats in the market. The four formats can be switched over through OSD menu or by PFM820(UTC controller). This feature makes the camera to be compatible with most end users' existing HD/SD DVRs.

Multi-language OSD

OSD menu provides multiple image adjustments and function settings to meet the requirements of different monitoring scenes. The OSD menu includes configurations such as backlight mode, day/night, white balance, privacy mask and motion detect. The camera supports 11 languages for OSD menu, namely, Chinese, English, French, German, Spanish, Portuguese, Italian, Japanese, Korean, Russian and Polish.


Protection

The camera's outstanding reliability is unsurpassed due to its rugged design. The camera is protected against water and dust with IP67 ranking, making it suitable for indoor or outdoor environments. With working temperature range of -40 °C to +60 °C (-40 °F to +140 °F), the camera is designed for extreme temperature environments. Supporting ±30% input voltage tolerance, this camera suits even the most unstable power supply conditions. Its 4KV lightning rating provides protection against the camera and its structure from the effects of lightning.


Technical Specification						Smart IR	Yes
Camera						Electronic Defog	Yes
Image Sensor	1/2.7 inch CMOS					Mirror	Off/On
Effective Pixels	1920(H)×1080(V), 2MP					Privacy Masking	Off/On (8 area, rectangle)
Scanning System	Progressive					Certifications	
Electronic Shutter Speed	PAL: 1/25s~1/100000s NTSC: 1/30s~1/100000s					Certifications	CE (EN55032:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN55024:2010+A1:2015, EN 55035:2017, EN 50130-4:2011+A1:2014), EN62368-1:2014 + A11:2017 FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1-07)
S/N Ratio	>65dB					Port	
Minimum Illumination	0.02Lux/F1.9, 30IRE, 0Lux IR on					Audio Output	One channel built-in mic (-A)
Fill Light Working Distance	30 m (98.4 ft)					Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
IR On/Off Control	Auto; manual					Power	
IR LED Number	1					Power Supply	12V ±30% DC
Pan/Tilt/Rotation Range	Pan: 0°~360° Tilt: 0°~78° Rotation: 0°~360°					Power Consumption	Max 3.3W (12V DC, IR on)
Lens						Environment	
Lens Type	Fixed-focal					Operating Temperature	-40°C to +60°C (-40°F to 140°F); <95% (non-condensation)
Mount Type	M12					Storage Temperature	-40°C to +60°C (-40°F to 140°F); <95% (non-condensation)
Focal Length	2.8 mm; 3.6 mm					Protection Grade	IP67
Max. Aperture	F1.9					Structure	
Field of View	2.8 mm: 119° x 101° x 54° (diagonal x horizontal x vertical) 3.6 mm: 100° x 84° x 45° (diagonal x horizontal x vertical)					Casing	Metal upper dome+plastic lower dome+plastic cover
Iris Type	Fixed iris					Camera Dimensions	φ97.0 mm x 85.8 mm (φ3.82" x 3.38")
Close Focus Distance	2.8 mm: 0.5 m (1.7 ft) 3.6 mm: 0.8 m (2.6 ft)					Net Weight	0.22 Kg (0.49 lb)
DORI Distance	Lens	Detect	Observe	Recognize	Identify	Gross Weight	0.28 Kg (0.62 lb)
	2.8 mm	38.6 m (126.6 ft)	15.4 m (50.5 ft)	7.7 m (25.3 ft)	3.9 m (12.8 ft)		
	3.6 mm	49.7 m (163.1 ft)	19.9 m (65.3 ft)	9.9 m (32.5 ft)	5 m (16.4 ft)		
Video							
Frame Rate	CVI: 1080P@25/30fps; 720P@25/30fps; 720P@50/60fps; AHD: 1080P@25/30fps; 720P@25/30fps; TVI: 1080P@25/30fps; 720P@25/30fps; 720P@50/60fps; CVBS: 960H						
Resolution	1080P (1920×1080); 720P (1280×720); 960H (960×576/960×480)						
Day/Night	Auto switch by ICR						
BLC	BLC/HLC/DWDR						
WDR	DWDR						
White Balance	Auto; manual						
Gain Control	Auto; manual						
Noise Reduction	2D NR						

Ordering Information

Type	Part Number	Description
2MP Camera	DH-HAC-HDW1200TL-A 2.8mm	2MP HDCVI IR Eyeball Camera
	DH-HAC-HDW1200TLN-A 2.8mm	
	DH-HAC-HDW1200TL-A 3.6mm	
	DH-HAC-HDW1200TLN-A 3.6mm	
Accessories	PFA13G	Junction Box
	PFB205W	Wall Mount Bracket (For use alone or with PFA152-E)
	PFA152-E	Pole Mount Bracket (For use with PFB205W)
	PFA12A	Plastic Junction Box
	PFA106	Mount Adapter (For use with PFB220C)
	PFB220C	Ceiling Mount Bracket (For use with PFA106)
	PFM800-E	Passive HDCVI Balun
	PFM321D	12V 1A Power Adapter
	PFM820	UTC Controller
	PFM904	Integrated Mount Tester



Dimensions (mm[inch])



Accessories

Optional:



PFA13G
Junction Box



PFB205W
Wall Mount Bracket
(For use alone or with PFA152-E)



PFA152-E
Pole Mount Bracket
(For use with PFB204W)



PFA12A
Plastic Junction Box



PFA106
Mount Adapter (For use with PFB220C)



PFB220C
Ceiling Mount Bracket (For use with PFA106)



PFM800-E
Passive HDCVI Balun



PFM321D
12V 1A Power Adapter



PFM820
UTC Controller



PFM904
Integrated Mount Tester