

DH-HAC-HDW1500TRQ(-A)

5MP Starlight HDCVI Quick-to-install IR Eyeball Camera



* The parameters and datasheets below can only be applied to 1500-S2 series.

- Max 25 fps@5MP (16:9 video output)
- Quick-to-install eyeball saves installation time
- Built-in mic (-A)
- CVI/CVBS/AHD/TVI switchable
- 3.6 mm fixed lens (2.8 mm optional)
- Max. IR length 25 m, Smart IR
- IP50, DC12V



System Overview

Experience 5MP full HD video and the simplicity of using existing cabling infrastructure with HDCVI. The Lite series 5MP HDCVI camera features a compact design and offers a high quality image at a friendly price. It offers various motorized/fixed lens models with a multi-language OSD and HD/SD switchable output. Its structural flexibility and high cost-performance makes the camera an ideal choice for SMB solutions.

Functions

4 Signals over 1 Coaxial Cable

HDCVI technology supports 4 signals to be transmitted over 1 coaxial cable simultaneously, i.e. video, audio*, data and power. Dual-way data transmission allows the HDCVI camera to interact with the XVR, such as sending control signal or triggering alarm. Moreover, HDCVI technology supports PoC for construction flexibility.

* Audio input is available for some models of HDCVI cameras.

Easy Installation

HDCVI Quick-to-install eyeball adopts quick-to-install pedestal, which can achieve easier installation than conventional eyeball. Quick-to-install camera reduces time and labor costs.

Long Distance Transmission

HDCVI technology guarantees real-time transmission at long distance without any loss. It supports up to 700 m for 5MP HD video via coaxial cable, and up to 300 m via UTP cable.*

*Actual results verified by real-scene testing in Dahua's test laboratory.

Simplicity

HDCVI technology inherits the feature of simplicity from traditional analog surveillance system, making itself a best choice for investment protection. HDCVI system can seamlessly upgrade the traditional analog system without replacing existing coaxial cabling. The plug and play approach enables full HD video surveillance without the hassle of configuring a network.

Smart IR

The camera is designed with IR LED illumination for best lowlight performance. Smart IR is a technology that ensures brightness uniformity in B/W image under low illumination. Dahua's unique Smart IR adjusts to the intensity of camera's infrared LEDs to compensate for the distance of an object, and prevents IR LEDs from overexposing images as the object come closer to the camera.

Multi-formats

The camera supports multiple video formats including HDCVI, CVBS and other two common HD analog formats in the market. The four formats can be switched over through OSD menu. This feature makes the camera to be compatible with most end users' existing HD/SD DVRs.




Multi-language OSD

OSD menu provides multiple image adjustments and function settings to meet the requirements of different monitoring scenes. The OSD menu includes configurations such as backlight mode, day/night, white balance, privacy mask and motion detect. The camera supports 11 languages for OSD menu, namely, Chinese, English, French, German, Spanish, Portuguese, Italian, Japanese, Korean, Russian and Polish.

Protection

With working temperature range of -40°C to +50°C (-40°F to 122°F), the camera is designed for extreme temperature environments. Supporting ±30% input voltage tolerance, this camera suits even the most unstable power supply conditions. Its 4KV lightning rating provides protection against the camera and its structure from the effects of lightning.

Technical Specification						WDR	DWDR
Camera						White Balance	Auto; manual
Image Sensor	1/2.7 inch CMOS					Gain Control	Auto; manual
Max. Resolution	2880 (H) × 1620 (V)					Noise Reduction	2D NR
Pixel	5MP					Smart IR	Yes
Scanning System	Progressive					Mirror	Off/On
Electronic Shutter Speed	PAL: 1/25 s~1/100,000 s NTSC: 1/30 s~1/100,000 s					Privacy Masking	Off/On (8 areas, rectangle)
S/N Ratio	> 65 dB					Certifications	
Min. Illumination	0.005 Lux/F1.6 30IRE, 0 Lux IR on					Certifications	CE (EN 55032:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 55024:2010+A1:2015, EN 55035:2017, EN 50130-4:2011+A1:2014, EN 62368-1:2014+A11:2017) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)
Illumination Distance	25 m (82.0 ft)					Port	
Illuminator On/Off Control	Auto; manual					Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Illuminator Number	2					Audio Interface	One channel built-in mic (-A)
Pan/Tilt/Rotation Range	Pan: 0°~360° Tilt: 0°~78° Rotation: 0°~360°					Power	
Lens						Power Supply	12V ±30% DC
Lens Type	Fixed-focal					Power Consumption	Max 3.0W (12V DC, IR on)
Mount Type	M12					Environment	
Focal Length	2.8 mm; 3.6 mm					Operating Temperature	-40°C to +50°C (-40°F to 122°F); < 95% (non-condensation)
Max. Aperture	F1.6					Storage Temperature	-40°C to +50°C (-40°F to 122°F); < 95% (non-condensation)
Field of View	2.8 mm: 132° × 111° × 58° (diagonal × horizontal × vertical) 3.6 mm: 109° × 92° × 48° (diagonal × horizontal × vertical)					Protection Grade	IP50
Iris Type	Fixed iris					Structure	
Close Focus Distance	2.8 mm: 0.9 m (3.0 ft) 3.6 mm: 1.6 m (5.2 ft)					Casing	Plastic
DORI Distance	Lens	Detect	Observe	Recognize	Identify	Dimensions	Φ97.1 mm × 93.0 mm (Φ3.82" × 3.66")
		2.8 mm	63.6 m (208.7 ft)	25.4 m (83.3 ft)	12.7 m (41.7 ft)	Net Weight	0.17 kg (0.37lb))
		3.6 mm	80 m (262.5 ft)	32 m (105.0 ft)	16 m (52.5 ft)	Gross Weight	0.23 kg (0.51lb)
Video							
Frame Rate	CVI: PAL: 5M@25 fps; 4M@25 fps; 1080P@25 fps; NTSC: 5M@25 fps; 4M@30 fps; 1080P@30 fps AHD: PAL: 4M@25 fps; NTSC: 4M@30 fps TVI: PAL: 4M@25 fps; NTSC: 4M@30 fps CVBS: PAL: 960H; NTSC: 960H						
	Resolution 5M (2880 × 1620); 4M (2560 × 1440); 1080P (1920 × 1080); 960 H (960 × 576/960 × 480)						
Day/Night	Auto switch by ICR						
BLC	BLC/HLC/DWDR						

Ordering Information			Accessories			
Type	Part Number	Description	Optional:			
SMP Camera	DH-HAC-HDW1500TRQP 2.8 mm	SMP HDCVI IR Eyeball Camera, PAL		PFA13G Junction Box		PFB205W Wall Mount Bracket
	DH-HAC-HDW1500TRQP 3.6 mm	SMP HDCVI IR Eyeball Camera, PAL		PFA152-E Pole Mount Bracket (For use with PFB205W)		
	DH-HAC-HDW1500TRQN 2.8 mm	SMP HDCVI IR Eyeball Camera, NTSC		PFM800-4K Passive HDCVI Balun		PFM321D 12V 1A Power Adapter
	DH-HAC-HDW1500TRQN 3.6 mm	SMP HDCVI IR Eyeball Camera, NTSC				PFM904 Integrated Mount Tester
	DH-HAC-HDW1500TRQP-A 2.8 mm	SMP HDCVI IR Eyeball Camera, PAL				
	DH-HAC-HDW1500TRQP-A 3.6 mm	SMP HDCVI IR Eyeball Camera, PAL				
	DH-HAC-HDW1500TRQN-A 2.8 mm	SMP HDCVI IR Eyeball Camera, NTSC		Junction Mount		Wall Mount
	DH-HAC-HDW1500TRQN-A 3.6 mm	SMP HDCVI IR Eyeball Camera, NTSC		Ceiling Mount		
	PFA13G	Junction Box				
	PFB205W	Wall Mount Bracket				
Accessories	PFA152-E	Pole Mount Bracket (For use with PFB205W)		Pole Mount (Vertical)		
	PFM800-4K	Passive HDCVI Balun				
	PFM321D	12V 1A Power Adapter				
	PFM904	Integrated Mount Tester				

Dimensions (mm[inch])

