

Tiandy

اردیبهشت 1405

هیچ نیازی از سوی کاربر بی پاسخ نمی ماند


NETWORK CAMERA - NVR
TIANDY



۰۲۱۵۲۶۰۵

tiandy-cctv.com

تارتن دژ آریانا
CCTV AND SECURITY SYSTEMS



BULLET SERIES

AK



TC-C321N
Spec:13/E/Y/2.8mm

- Max. Resolution: 2MP
- Image Sensor: 1/3" CMOS
- Min. Illumination: Color: 0.04 Lux
- Wide Dynamic Range: DWDR
- IR LEDs: 2
- IR Distance: 30 m
- Built-in Mic: Yes
- Alarm I/O: N/A
- On-board Storage: N/A
- Housing: Plastic + Metal
- Video Analytics: Tripwire; Perimeter

66,000,000 R

AK



TC-C321N 1CNB-28

- Max. Resolution : 2MP
- Image Sensor : 1/3" CMOS
- Min. Illumination :Color:0.02Lux
- Wide Dynamic Range : DWDR
- IR LEDs : 2
- IR Distance : Up to 30m
- Built-in Mic : 1YES
- Alarm I/O : N/A
- On-board Storage : N/A
- Housing : Metal+plastic housing
- Video Analytics : N/A

68,000,000 R

AK



TC-C321N
Spec:AK/I3W/E/Y/2.8mm/V2.0

- Plastic housing
- Up to 2MP,1920x1080@30fps
- S+265/H.265/H.264B/H.264M/H.264H
- Color:0.02Lux@(F1.6,AGC ON),B/W:0Lux with IR
- IR range up to 30m
- 1xBuilt-in Mic
- Operating conditions -30°C~60°C (-22°F~140°F), ≤95%RH
- PoE:IEEE 802.3af,Max. 3W
- IP67

79,000,000 R

AK



TC-C321N 1ANB-28

- Max. Resolution : 2MP
- Image Sensor : 1/3"CMOS
- Min. Illumination :Color:0.02Lux
- Wide Dynamic Range : DWDR
- IR LEDs : 2
- IR Distance : Up to 30m
- **Dual light + 15m White LED**
- Built-in Mic : 1YES
- Alarm I/O : N/A
- On-board Storage : N/A
- Video Analytics : N/A

79,000,000 R

Spark



TC-C32QN
Spec:13/E/Y/2.8mm/V5.1

- Max. Resolution: 2MP
- Image Sensor: 1/2.9" CMOS
- Min. Illumination: Color: 0.02 Lux
- Wide Dynamic Range: DWDR
- IR LEDs: 2
- IR Distance: Up to 30 m
- Built-in Mic: Yes
- Alarm I/O: N/A
- On-board Storage: N/A
- Housing: Metal + Plastic
- Video Analytics: Tripwire; Perimeter

79,350,000 R

Spark



TC-C32QN
Spec:15W/E/Y/V4.2

- Metal+plastic housing
- Up to 2MP,1920x1080@30fps
- S+265/H.265/H.264B/H.264M/H.264H
- Color:0.02Lux@(F1.6,AGC ON),B/W:0Lux with IR
- IR range up to 50m
- 1xBuilt-in Mic
- Operating conditions -30°C~60°C (-22°F~140°F), ≤95%RH
- DC12V±25%,Max. 6.5W, PoE:IEEE 802.3af,Max. 7W
- IP67

105,000,000 R

Spark



TC-C34QN
Spec:13/E/Y/2.8MM(4mm)/V5.0

- Max. Resolution: 4MP
- Image Sensor: 1/2.9" CMOS
- Min. Illumination: Color: 0.02 Lux
- Wide Dynamic Range: DWDR
- IR LEDs: 2
- IR Distance: Up to 30 m
- Built-in Mic: Yes
- Alarm I/O: N/A
- On-board Storage: N/A
- Housing: Metal + Plastic, Bullet type, IP67
- Video Analytics: Tripwire, Perimeter

113,620,000 R

Super lite




TC-C32GS
15/E/Y/C/SD/2.8MM/V4.2

- Max. Resolution : 2MP
- Image Sensor : 1/2.8"CMOS
- Min. Illumination :Color:0.002Lux
- Wide Dynamic Range : 120dB WDR
- IR LEDs : 2
- IR Distance : Up to 50m
- Built-in Mic : Yes
- Alarm I/O : N/A
- On-board Storage : microSD up to 512 GB
- Housing : Metal+plastic housing
- Video Analytics : Tripwire; Perimeter

103,000,000 R

Super lite



TC-C34GN
Spec:15/E/Y/C/2.8mm/V4.2

- Max. Resolution : 4MP
- Image Sensor : 1/2.7"CMOS
- Min. Illumination : 0.02Lux
- Wide Dynamic Range : DWDR
- IR range up to 50m
- IR LEDs : 2
- IR Distance : Up to 50m
- Built-in Mic : Yes
- Alarm I/O : N/A
- On-board Storage : N/A
- Housing : Metal+plastic housing
- Video Analytics : Tripwire; Perimeter

117,300,000 R

Super lite



TC-C34QN
Spec:15W/E/Y/2.8MM/V4.2

- Max. Resolution : 4MP
- Image Sensor : 1/2.9"CMOS
- Min. Illumination : Color:0.02Lux
- Wide Dynamic Range : 120db WDR
- IR LEDs : 2 Warm Light
- IR Distance : Up to 50m
- Built-in Mic : Yes
- Alarm I/O : N/A
- On-board Storage : N/A
- Housing : Metal+plastic housing
- Video Analytics : Tripwire; Perimeter

147,000,000 R

Super lite



TC-C34GS
15/E/Y/C/SD/2.8MM/V4.2

- Max. Resolution : 4MP
- Image Sensor : 1/2.7"CMOS
- Min. Illumination : Color:0.002Lux
- Wide Dynamic Range : DWDR
- IR LEDs : 2
- IR Distance : up to 50m
- Built-in Mic : Yes
- Alarm I/O : N/A
- On-board Storage : microSD up to 512GB
- Housing : Metal+plastic housing
- Video Analytics : Tripwire; Perimeter

142,800,000 R


Lite



TC-C35WS 3ERA-28


- Max. Resolution : 5MP
- Image Sensor : 1/2.7" CMOS
- Min. Illumination :Color:0.002Lux
- Wide Dynamic Range : 120 db
- IR LEDs : 2
- IR Distance : Up to 50m
- **Dual light + 15m white LED**
- Built-in Mic : 1YES
- Alarm I/O : N/A
- On-board Storage : microSD up to 512GB
- Housing : **Metal housing**
- Video Analytics : Human/Vehicle Classification; Tripwire; Perimeter

230,000,000 R



BULLET SERIES

Pro



TC-C35US

Spec: I8/A/E/Y/M/S/H/2.7-13.5mm/V4.0

- Max. Resolution :Up to 5MP,2880×1620@30fps
- Image Sensor : 1/2.7"CMOS
- Min. Illumination :Color:0.002Lux@(F1.6,AGC ON),B/W:0Lux with IR
- Wide Dynamic Range : 120dB
- IR LEDs : 4
- IR Distance : Up to 80m
- Built-in Mic : 1×Built-in Mic
- Alarm I/O : yes
- On-board Storage : Support microSD/microSDHC/microSDXC card,up to 512GB
- Housing : Metal housing
- Video Analytics :Human/Vehicle Classification; Tripwire; Perimeter; Video Abnormal; Audio Abnormal

330,000,000 R

WIFI



TC-H332A













Spec: I2W/WIFI/Eu/4mm


- Max. Resolution : 3MP
- Image Sensor : 1/3"CMOS
- Min. Illumination :Color:0.02Lux
- Wide Dynamic Range : DWDR
- IR LEDs : 4
- IR Distance : Up to 15m
- **Dual light + 8m white LED**
- Built-in Mic : 1YES
- Alarm I/O : N/A
- On-board Storage : microSD up to 512GB
- Housing : Plastic housing
- Video Analytics : Smart Alarm

102,925,000 R



DOME SERIES

<p>AK</p>  <p>TC-C320N <u>Spec:I3/E/Y/2.8mm</u></p> <ul style="list-style-type: none"> Max. Resolution : 2MP Image Sensor : 1/2.9"CMOS Min. Illumination : Color:0.02Lux Wide Dynamic Range : DWDR IR LEDs : 2 IR Distance : Up to 30m Built-in Mic : YES Alarm I/O : N/A On-board Storage : N/A Housing : Metal+plastic housing Video Analytics : N/A <p>66,000,000 R</p>	<p>AK</p>  <p>TC-C320N 1CNB-28</p> <ul style="list-style-type: none"> Max. Resolution : 2MP Image Sensor : 1/3"CMOS Min. Illumination :Color:0.02Lux Wide Dynamic Range : DWDR IR LEDs : 2 IR Distance : Up to 30m Built-in Mic : 1YES Alarm I/O : N/A On-board Storage : N/A Housing : Plastic housing Video Analytics : N/A <p>68,000,000 R</p>	<p>AK</p>  <p>TC-C320N <u>Spec:AK/I3W/E/Y/2.8mm/V2.0</u></p> <ul style="list-style-type: none"> Plastic housing Up to 2MP,1920×1080@30fps S+265/H.265/H.264B/H.264M/H.264H IR LEDs : 2 Color:0.02Lux@(F1.6,AGC ON),B/W:0Lux with IR IR range up to 30m 1×Built-in Mic Operating conditions -30°C~60°C (-22°F~140°F), ≤95%RH PoE:IEEE 802.3af,Max. 2.5W <p>79,000,000 R</p>	<p>AK</p>  <p>TC-C320N 1ANB-28</p> <ul style="list-style-type: none"> Max. Resolution : 2MP Image Sensor : 1/3"CMOS Min. Illumination :Color:0.02Lux Wide Dynamic Range : DWDR IR LEDs : 2 IR Distance : Up to 30m Dual light + 15m white LED Built-in Mic : 1YES Alarm I/O : N/A On-board Storage : N/A Housing : Plastic housing Video Analytics : N/A <p>79,000,000 R</p>
<p>Spark</p>  <p>TC-C32XN <u>Spec:I3/E/Y/2.8mm/V5.1</u></p> <ul style="list-style-type: none"> Max. Resolution : 2MP Image Sensor : 1/2.9"CMOS Min. Illumination : color:0.02Lux Wide Dynamic Range : DWDR IR LEDs : 2 IR Distance : Up to 30m Built-in Mic : YES Alarm I/O : N/A On-board Storage : N/A Housing : Metal+Plastic Housing Video Analytics : N/A <p>85,000,000 R</p>	<p>Spark</p>  <p>TC-C32XN <u>Spec:I3W/E/Y/2.8mm/V4.2</u></p> <ul style="list-style-type: none"> Metal+plastic housing Up to Max. Resolution S+265/H.265/H.264B/H.264M/H.264H Color:0.02Lux@(F1.6,AGC ON),B/W:0Lux with IR IR Range 30m Built-in Mic Support Smart surveillance Operating Conditions -30°C~60°C(No turning on the light), Humidity 95% or less (no condensation) DC12V±25%,MAX 6.5W, POE 802.3af,MAX 7W <p>105,000,000 R</p>	<p>Spark</p>  <p>TC-C34XN <u>Spec:I3/E/Y/2.8MM/V5.0</u></p> <ul style="list-style-type: none"> Max. Resolution : 4MP Image Sensor : 1/3"CMOS Min. Illumination : Color:0.02Lux Wide Dynamic Range : DWDR IR LEDs : 2 IR Distance : Up to 30m Built-in Mic : YES Alarm I/O : N/A On-board Storage : N/A Housing : Metal+Plastic Housing Video Analytics : Tripwire;Perimeter <p>117,000,000 R</p>	<p>Super lite</p>  <p>TC-C34HN <u>I3/E/Y/C/2.8mm/V4.2</u></p> <ul style="list-style-type: none"> Metal+plastic housing Up to 4MP,2688×1520@25fps S+265/H.265/H.264B/H.264M/H.264H Color:0.02Lux@(F1.6,AGC ON),B/W:0Lux with IR IR range up to 30m 1×Built-in Mic Operating conditions -30°C~60°C(-22°F~140°F), ≤95%RH PoE:IEEE 802.3af,Max. 6W IP66 <p>112,000,000 R</p>
<p>Super lite</p>  <p>TC-C34XN <u>Spec:I3W/E/Y/2.8MM/V4.2</u></p> <ul style="list-style-type: none"> Max. Resolution : 4MP Image Sensor : 1/2.9"CMOS Min. Illumination : Color:0.02Lux Wide Dynamic Range : 120dB IR LEDs : 2 Warm Light IR Distance : Up to 30m Built-in Mic : YES Alarm I/O : N/A On-board Storage : N/A Housing : Metal+plastic housing Video Analytics : Tripwire; Perimeter <p>143,000,000 R</p>	<p>Super lite</p>  <p>TC-C34KS <u>Spec:I3/E/Y/2.8mm</u></p> <ul style="list-style-type: none"> Max. Resolution : 4MP Image Sensor : 1/2.8" CMOS Min. Illumination : Color: 0.002Lux Wide Dynamic Range : 120dB WDR IR LEDs : 8 IR Distance : Up to 30m Built-in Mic : YES Alarm I/O : N/A On-board Storage : MicroSD up to 512 GB Housing : Metal+Plastic Housing Video Analytics : Tripwire, Perimeter <p>203,550,000 R</p>	<p>Lite</p>  <p>TC-C34XP <u>SPEC: W/E/Y/2.8MM/V4.0</u></p> <ul style="list-style-type: none"> Max. Resolution : 4MP Image Sensor : 1/2.8" CMOS Min. Illumination : Color: 0.0008Lux@ (F1.0, ACG ON), 0Lux with LED on Wide Dynamic Range : 120dB WDR IR LEDs : N/A IR Distance : - Built-in Mic : YES Alarm I/O : N/A On-board Storage : MicroSD up to 512 GB Housing : Metal+Plastic Housing Video Analytics : Tripwire, Perimeter <p>201,250,000 R</p>	<p>Lite</p>  <p>TC-C35KS <u>Spec:I3/E/Y/2.8mm/v4.0</u></p> <ul style="list-style-type: none"> Max. Resolution : 5MP Image Sensor : 1/2.8" CMOS Min. Illumination : Color: 0.002Lux Wide Dynamic Range : 120dB WDR IR LEDs : 8 IR Distance : Up to 30m Built-in Mic : YES Alarm I/O : N/A On-board Storage : MicroSD up to 512 GB Housing : Metal+Plastic Housing Video Analytics : Tripwire, Perimeter <p>228,000,000 R</p>



DOMESERIES

Pro




TC-C35MS

SPEC: I3/A/E/Y/M/C/H/2.7- 13.5MM/V4.0

- Max. Resolution : 5MP
- Image Sensor : 1/2.8" CMOS
- Min. Illumination : Color: 0.002Lux
- Wide Dynamic Range : 120dB WDR
- IR LEDs : 18
- IR Distance : Up to 30m
- Built-in Mic : YES
- Alarm I/O : Yes
- On-board Storage : microSD to 512GB
- Housing : Metal+plastic housing
- Video Analytics : Tripwire; Perimeter

253,000,000 R



SPEED-DOME SERIES



TC-H324S
Spec:23X/I/E/C/V3.0

- 2MP
- Up to 1920X1080@30fps
- Optical zoom: 23x
- Smart IR, IR Range: 150m
- S+265/H.265/H.264/M-JPEG
- Intelligent monitoring
- Support Human/Vehicle Classification
- Plugin Free
- IP66

770,000,000 R



TC-H324S
SPEC:25X/I/E/V3.0

- 2MP
- Up to 1920X1080@30fps
- Min. illumination Color: 0.001Lux@F1.5
- Optical zoom: 25x, digital zoom 16x
- Support Human/Vehicle Classification
- Smart IR,
- IR Range: 150m S+265/H.265/H.264/M-JPEG Plugin Free
- IP66

1,050,000,000 R



TC-H326S
SPEC:33X/I/E+/A/V3.0

- 2MP
- Up to 1920X1080@30fps
- Min. illumination Color: 0.001Lux@F1.5 - Smart IR,
- Optical zoom: 33x, digital zoom 16x
- IR Range: 200m - S+265/H.265/H.264/M-JPEG - Intelligent monitoring/ Face Capture mode Support Human/Vehicle Classification - Support Auto-tracking
- Plugin Free - IP66

1,400,000,000 R



TC-H366V
Spec:4MP/25X/IW/E/A/2.8mm

- 6MP
- Detail:2560x1440@25fps
- Panorama:0.0001lux Detail:0.001Lux
- Panorama:S+265/H.265/H.264/M-JPEG
- Detail:S+265/H.265/H.264/M-JPEG
- Built-in Micro SD card slot, up to 512 GB
- Support Panorama:Smart surveillance Detail:Smart surveillance
- Support Panorama:Human/Vehicle Classification
- Detail:Human/Vehicle Classification
- Operating Conditions -30°C~65°C(IR OFF) -30°C~40°C(IR ON), 0-95%
- AC24V±25%\DC24V±10%, POE IEEE802.3BT
- IP66

1,725,000,000 R



TC-H344S
Spec:25X/I/E+/A/V3.0

- 4MP
- Color:0.001lux@ (F1.6,AGC ON),B/W:0lux with IR
- S+265/H.265/H.264B/H.264M/H.264H/Motion JPEG
- Optical zoom 25X
- IR range up to 150m
- Support microSD/microSDHC/microSDXC card,up to 512GB
- Support smart surveillance, detect up to 32 faces at the same scene
- Support human/vehicle classification
- Operating conditions -30°C~65°C(-22°F~149°F), ≤95%RH
- DC12V±10%, PoE:IEEE 802.3at
- IP66

1,220,000,000 R



TC-H348M
Spec:63X/IL/E++/A

- 4MP
- Color:0.001lux@ (F1.6,AGC ON),0lux with IR
- S+265/H.265/H.264B/H.264M/H.264H
- Optical zoom 63X
- IR range up to 300m
- Support microSD/microSDHC/microSDXC card,up to 512GB
- Support smart surveillance, detect up to 32 faces at the same scene
- Support human/vehicle classification
- Operating conditions -40°C~70°C(-40°F~158°F), ≤95%RH
- DC36V±25%, PoE:IEEE 802.3bt
- IP66

تماس بگیریید



NVR SERIES



TC-R3104

Spec:I/B/P4/C/Eu/L/S/V2.0

- Up to 4-ch IP camera accesses
- Incoming/Outgoing bandwidth: 60Mbps/40Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 6MP(30fps)×1 or 1080P(30fps)×4
- 4-ch synchronous playback
- Up to 8 TB capacity for each HDD
- Simultaneous HDMI and VGA outputs
- HDMI output at up to 1080P resolution
- 1×RJ-45, 10/100 Mbps self-adaptive Ethernet port
- PoE interface, 4×RJ45, 10/100 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Support cloud upgrade

159,000,000 R



TC-R3105

Spec:I/B/L/S

- Up to 5-ch IP camera accesses
- Incoming/Outgoing bandwidth: 60Mbps/40Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 5MP(30fps)×1 or 1080P(30fps)×2
- 4-ch synchronous playback
- Up to 6 TB capacity for each HDD
- 1×HDMI output
- HDMI output at up to 1080P resolution
- 1×RJ-45, 10/100 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Support cloud upgrade

125,350,000 R



TC-R3108

Spec: I/B/P8/C/Eu/L/S

- Up to 8-channel input
- 8 PoE ports
- Up to 6MP Resolution Recording

185,000,000 R



TC-R3120

Spec:I/B/V3.0

- HD Input
- +265/H.265/H.264 video formats
- Connectable to the third-party network cameras
- Up to 20-channel input
- Supports live view, storage, and playback of the connected camera at up to 8MP resolution

313,950,000 R



TC-R3220 4HA

AI NVR

- Up to 20-ch IP camera accesses
- Incoming/Outgoing bandwidth: 160Mbps(AI on: 120Mbps)/80Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 16MP(30fps)×1 or 1080P(30fps)×10
- 16-ch synchronous playback
- Up to 10 TB capacity for each HDD
- Simultaneous HDMI and VGA outputs
- HDMI output at up to 4K resolution
- 1×RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Support cloud upgrade

630,000,000 R



TC-R3232 4HA

- Up to 32-ch IP camera accesses
- Incoming/Outgoing bandwidth: 160Mbps(AI on: 120Mbps)/80Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 16MP(30fps)×1 or 1080P(30fps)×10
- 16-ch synchronous playback
- Up to 10 TB capacity for each HDD
- Simultaneous HDMI and VGA outputs
- HDMI output at up to 4K resolution
- 1×RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Support cloud upgrade

747,500,000 R



TC-R3432

Spec:I/B/K/V3.1

- Up to 32-ch IP camera accesses
- Incoming/Outgoing bandwidth: 160Mbps/48Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 8MP(30fps)×2 or 1080P(30fps)×8
- 16-ch synchronous playback
- Up to 10 TB capacity for each HDD
- Simultaneous HDMI and VGA outputs
- HDMI output at up to 4K resolution
- 2×RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Support cloud upgrade

880,000,000 R



TC-R3240

Spec:I/B/N/H/V4.1

- Up to 40-ch IP camera accesses
- Incoming/Outgoing bandwidth: 400Mbps/400Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 16MP(30fps)×2 or 1080P(30fps)×20
- 16-ch synchronous playback
- Up to 10 TB capacity for each HDD
- Independent HDMI and VGA outputs
- HDMI output at up to 4K resolution
- 2×RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Support cloud upgrade

890,000,000 R



TC-R3440

Spec:I/B/N/H/C/V4.0

- Up to 40-ch IP camera accesses
- Incoming/Outgoing bandwidth: 400Mbps/400Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 16MP(30fps)×2 or 1080P(30fps)×20
- Independent HDMI and VGA outputs
- HDMI output at up to 4K resolution
- 2×RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- 16-ch synchronous playback
- Support cloud upgrade
- Up to 10 TB capacity for each HDD

980,000,000 R



TC-R3440

Spec:I/B/N/V4.0

- Up to 40-ch IP camera accesses
- Incoming/Outgoing bandwidth: 400Mbps/400Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 16MP(30fps)×2 or 1080P(30fps)×20
- Independent HDMI and VGA outputs
- HDMI output at up to 4K resolution
- 2×RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- 16-ch synchronous playback
- Support cloud upgrade
- Up to 10 TB capacity for each HDD

1,200,000,000 R



TC-R3840

Spec:I/B/N/V4.0

- Up to 40-ch IP camera accesses
- Incoming/Outgoing bandwidth: 640Mbps/320Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 16MP(30fps)×4 or 1080P(30fps)×32
- 16-ch synchronous playback
- Up to 24 TB capacity for each HDD
- Simultaneous HDMI1 and VGA1 outputs; Simultaneous HDMI2 and VGA2 outputs
- HDMI output at up to 4K resolution
- 2×RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Support cloud upgrade

تماس بگیریید



TC-R3880

Spec:I/B/N/V4.0

- HD Input Transmission
- S+265/H.265/H.264 video formats
- Connectable to the third-party network cameras
- Up to 80 IP cameras can be connected
- Supports live view, storage, and playback of the connected camera at up to 12MP resolution
- HD Output HDMI and VGA independent outputs
- HDMI Video output at up to 4K (3840 X 2160) resolution
- HD Storage 8 SATA interfaces connectable for recording and backup, up to 10TB for each HDD
- S+265 compression effectively reduces the storage space and costs by up to 75%
- 2 self-adaptive 10/100/1000 Mbps network interfaces

تماس بگیریید

